



SUMMER, WINTER, ALL SEASON

BAR & CHAIN OIL

RIDGELINE™

PRODUCT DESCRIPTION AND APPLICATIONS

RIDGELINE™ BAR & CHAIN Oils are high quality fluids that are designed to withstand the tough requirements and operating conditions to keep you chainsaws well lubricated and at peak performance.

Recommended for use in all types of chain saws using manual or automatic oilers for lubrication of the bar, chain and sprocket. This may include (but not limited to) hand held and commercial machines. They are exceptional lubricants for open bearings, gears and chains found in industrial applications such as sawmills, woodlands, mining operations, or anywhere a tacky, nondrip oil and/or tacky red oil is required

RIDGELINE™ SUMMER

RIDGELINE™ BAR & CHAIN OIL SUMMER is a hi-tack bar and chain lubricant formulated for summer use. This heavy weight oil offers outstanding anti-wear protection and maintains its hi-tack during high heat operating conditions to keep your equipment running smoothly. Recommended operating temperature range is from 10° C to 45° C.

RIDGELINE™ WINTER

RIDGELINE™ BAR & CHAIN OIL WINTER has been specially formulated for lower ambient operating temperatures during the winter months. Its hi-tack attributes and greater flow rate allows the oil to adhere to the bar and chain to maintain protection and performance of high speed moving parts even in colder temperatures. Recommended operating temperature range is from -45° C to 0° C.

RIDGELINE™ ALL SEASON

RIDGELINE™ BAR & CHAIN OIL ALL SEASON is a premium formula specifically designed to fit a wide variety of ambient operating temperature ranges. The hi-tack All Season oil delivers protection and performance all year round for ease of mind and simplicity of inventory. Recommended operating temperature range is from -15° C to 30° C.

FEATURES AND BENEFITS

Bar and Chain Oil is specially formulated to protect your chain saw. Tackiness agent helps keep the oil on the chain even at high temperature and/or high speed operation.

- Prevents wear
- Reduces dripping and throw-off
- Clings to chain even at high temperatures and speed
- Protects your chain saw chain and bar
- Includes tackiness agent to keep oil on the chain
- Prevents premature chain wear at low and high temperatures
- Ideal to use in all weather conditions



Distributed by:

Parkland Corporation
1800, 240 4 Ave SW, Calgary, AB T2P 4H4

™ Trademark of Parkland Corporation

www.ridgelinelubricants.com
ridgeline.information@parklandusa.com

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	SUMMER	WINTER	ALL SEASON
Gravity, °API	ASTM D287	29.11	32.06	30.1
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.881	0.8651	0.8756
Flash Point, °C	ASTM D92	235	218	226
Flash Point, °F	ASTM D92	455	424	439
Viscosity @ 40°C, cSt	ASTM D445	237.6	92.46	153.6
Viscosity @ 100°C, cSt	ASTM D445	21.24	13.43	16.66
Viscosity Index	ASTM D2270	106	146	116
Pour Point, °C, (°F)	ASTM D5950	-30°C (-22°F)	-39°C (-38°F)	-36°C (-33°F)
Color	ASTM D1500	Red	Red	Red

The physical property values above are typical of normal production and may vary.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity.
Parkland Fuel Corporation takes no responsibility for product misuse or misapplication.

Distributed by:
Parkland Corporation
1800, 240 4 Ave SW, Calgary, AB T2P 4H4

™ Trademark of Parkland Corporation

www.ridgelinelubricants.com
ridgeline.information@parklandusa.com