

**INDUSTRIAL**

# **PROCESS OIL**

**ISO 32****RIDGELINE™**

## **PRODUCT DESCRIPTION**

RIDGELINE™ Process Oil is a good stability oil that meets requirements as a processing matrix or an extender oil.

## **FEATURES AND BENEFITS**

- Low deposit properties
- Rapid release of entrained air
- Low pour points

## **APPLICATIONS**

Can be utilized as plasticizers, carriers, diluents, and extenders in industrial material formulations and chemical processes.



Distributed by:  
**Parkland Corporation**  
1800, 240 4 Ave SW, Calgary, AB T2P 4H4

™ Trademark of Parkland Corporation

[www.ridgelinelubricants.com](http://www.ridgelinelubricants.com)  
[ridgeline.information@parklandusa.com](mailto:ridgeline.information@parklandusa.com)



## TYPICAL PROPERTIES

Property	Typical Properties
ISO Grade	32
ATSM D-1500	<0.5
Appearance	Bright/Clear
Viscosity, cSt at 100°C	5.2
Viscosity, cSt at 40°C	32
Flash Point (COC) DegF(C)	430(221)
Pour Pt, Deg C	10(-12)
Neut. No., ASTM D 974	<0.55
Gravity, API @ 60°F	31.5
Specific Gravity, 60°F	0.868

The physical property values above are typical of normal production and may vary.

## DISCLAIMER

Always follow OEM recommendations for fluid viscosity.  
Parkland Corporation takes no responsibility for product misuse or misapplication.

Distributed by:  
**Parkland Corporation**  
**1800, 240 4 Ave SW, Calgary, AB T2P 4H4**  
™ Trademark of Parkland Corporation  
[www.ridgeline lubricants.com](http://www.ridgeline lubricants.com)  
[ridgeline.information@parklandusa.com](mailto:ridgeline.information@parklandusa.com)

