

**INDUSTRIAL****DRIP OIL****RIDGELINE™****PRODUCT DESCRIPTION**

RIDGELINE™ Drip Oil is a good quality anti-wear hydraulic oil intended for industrial and mobile service applications, subjected to moderate operating conditions and requiring anti-wear lubricants.

FEATURES AND BENEFITS

- Good anti-wear performance helps reduce pump wear and prolonging pump life.
- Corrosion protection helps reduce the effects of moisture on system components.
- Filterability to prevent filter blockage even in the presence of water.

APPLICATIONS

- Systems using gear, vane, radial and axial piston pumps and those containing gears and bearings where mild anti-wear characteristics are required.
- Where hydraulic oil contamination or leakage is unavoidable.
- Where small amounts of water are unavoidable.

Distributed by:
Parkland Corporation
1800, 240 4 Ave SW, Calgary, AB T2P 4H4

™ Trademark of Parkland Corporation

www.ridgelinelubricants.com
ridgeline.information@parklandusa.com



SPECIFICATIONS

RIDGELINE™ Drip Oil meets the requirements of the following specifications:

Claims	DRIP OIL
DIN 51524-2:2006-09	●
ISO L-HM (ISO 11158:1997)	●
DENISON HF-0	★
★ = Approved ● = Meets Requirements ○ = Suitable for Use	

TYPICAL PROPERTIES

Property	Test Method	DRIP OIL
Copper Strip Corrosion, 3 h, 100 C, Rating	ASTM D130	1A
Density @ 15 C, kg/l	ASTM D1298	0.872
Emulsion, Time to 3 mL Emulsion, 54 C, min	ASTM D1401	15
Flash Point, Cleveland Open Cup, °C	ASTM D92	212
Kinematic Viscosity @ 100 C, mm ² /s	ASTM D445	5.3
Kinematic Viscosity @ 40 C, mm ² /s	ASTM D445	31.4
Pour Point, °C	ASTM D97	-24
Viscosity Index	ASTM D2270	98

The physical property values above are typical of normal production and may vary.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity.
Parkland Corporation takes no responsibility for product misuse or misapplication.

Distributed by:
Parkland Corporation
1800, 240 4 Ave SW, Calgary, AB T2P 4H4
 ™ Trademark of Parkland Corporation
www.ridgelinelubricants.com
ridgeline.information@parklandusa.com

